References:-

[1] A. H. M. Z. Alam, W. A. Lawal, S. Khan and M. M. Rashid, "Design of Multi-Valued Quaternary Based Analog-to-Digital Converter," American Journal of Applied Sciences, 6 (8): 1522-1527 (2009).

[2] A. I. Stanley, Eke James and F. U. Nweke, "The use of SOA-based Mach-Zende Interferometer in Designing/Implementing All-optical Integrated Full Adder-Subtractor and Demultiplexer" I.J.E.M.S., 6 (1), 40-44 (2015).

[3] A. J. Poustie and K. J. Blow, "Demonstration of an all-optical Fredkin gate" Optics Communications, DOI: 10.1016/S0030-4018(99)00722-1 (2000).

[4] Ajay Kumar, Santosh Kumar, Sanjeev Kumar Raghuwanshi, "Implementation of XOR/XNOR and AND logic gates by using Mach–Zehnder interferometers" Optik - Int. J. Light Electron Opt., doi.org/10.1016/j.ijleo.2014.07.037 (2014).

[5] Alaa A. Al-Saffar and Doaa A. Karim, "Quaternary Division Operation based on All-Terahertz Optical Asymmetric Demultiplexer (TOAD)" International Journal of Advances in Engineering & Technology, IJAET ISSN: 22311963, 7 (1), 38-49 (2014).

[6] Ali Hajjiah, Abdullah Alqallaf and Abdallah Cherri, "Designs of All-Optical Higher-Order Signed-Digit Adders Using Polarization-Encoded Based Terahertz-Optical-Asymmetric-Demultiplexer (TOAD)" Optics and Photonics Journal, 4, 113-128 (2014).

[7] Animesh Bhattacharya, Amal K Ghosh,Goutam K Maity,Kazi A H TaslimArif " SLM and savart Plate Based Optical Quadruple D Flip Flop Using Reversible Quadraple Logic Gates" International Conference on "Advances in Science & Technology" (ICAST -2017), ISBN: 978-1-945919-47-3, March 17th–19th, 2017.

[8] C. Reis1, L. Costa1, A. Bogoni, A. Maziotis, A. Teixeira1, C. Kouloumentas, D. Apostolopoulos, D. Erasme, G. Berrettini, G. Meloni, G. Parca1, H. Brahmi, I. Tomkos, L. Poti, M. Bougioukos, P. S.Andre, P. Zakynthinos, R. Dionisio1, T. Chattopadhyay, H. Avramoupoulos, "Evolution of All-Optical Flip-Flops and Their Applications in Optical Communications Networks" IEEE , Optoelectronics, IET , 6 (6),10.1049/iet-opt.2012.0012 (2012).

[9] C. Schubert, et. al., “160-Gbit/s all-optical demultiplexing using a gain-transparent ultrafastnonlinear interferometer (GT-Uni),” IEEE Photon. Technol. Lett., 13,475–477 (2001).

[10] Chinmoy Taraphdar, Tanay Chattopadhyay and Jitendra Nath Roy, “Mach–Zehnder interferometer-based all-optical reversible logic gate” Optics & Laser Technology 42, 249–259 (2010).

[11] D. K. Gayen and J. N. Roy, “All-Optical Arithmetic Unit with the help of Terahertz Optical Asymmetric Demultiplexer (TOAD) based Tree Architecture,” Applied Optics, 47(7), 933-943 (2008).

[12] D. M. Miller, et al., “Transformation-based Synthesis of Networks of Toffoli/ Fredkin Gates,” IEEE Xplore (2009).

[13] D. Song, V. Gauss, H. Zhang, M. Gross, P. Wen, and S. Esener, “All-optical flip-flop based on vertical cavity semiconductor optical amplifiers,” Optics Letters, 32 (20), 2969-2971 (2007).

[14] Dilip Kumar Gayen, Tanay Chattopadhyay, Arunava Bhattacharyya, Saikat Basak, Dipanti Dey, "All-optical half-adder/half-subtractor using terahertz optical asymmetric demultiplexer",Applied Optics, Vol. 53, Issue 36, pp. 8400-8409 (2014).

[15] Dilip Kumar Gayena, Jitendra Nath Roy and Rajat Kumar Pal, “All-optical carry lookahead adder with the help of terahertz optical asymmetric demultiplexer” Optik, Optik 123, 40-45 (2012).

[16] E. V. Dubrova, “Multiple-Valued Logic in VLSI Design,” Electronic System Design, Royal Institute of Technology, Sweden (2000).

[17] G. K. Maity, J. N. Roy, S. P. Maity: “Mach-Zehnder interferometer based all-optical Peres Gate”.Proc. of first International Conference on Advances in Computing and Communications (ACC-2011), Kochi, India, Lecture Notes in Computer Science, Springer, Vol. 192, Part 3, pp. 249-258, July 2011.

[18] G. P. Agrwal, “Fibre- optic Communication Systems (3rd edition) [John Wiley & sons,” INC publication, New York (2002).

[19] Goutam Kumar Maity, Ashis Kumar Mandal,Nabin B Manik,“All-optical programmable Binary-to-Gray or Gray-to-Binary Code Converter using TOAD based

Reversible New Multiplexer" *Optik Optik - International Journal for Light and Electron Optics(Elsevier), Volume 127, Issue 18, September 2016, Pages 7167–7173 2016.*

[20] Goutam Kumar Maity, Tanay Chattopadhyay, Dilip Kumar Gayen, Chinmoy Taraphdar, Anup Kumar Maity, Santi Prasad Maity, Jitendra Nath Roy, "All-optical binary flip-flop with the help of Terahertz Optical Asymmetric Demultiplexer" Springer, DOI 10.1007/s11047-009-9162-8 (2010).

[21] H. Thapliyal and H. R. Arabnia, "Reversible Programmble Logic Array (RPLA) using Fredkin & Feynman Gates for Industrial Electronic and Applications," VLSI and Embedded System Technologies, IIIT, Hyderabad, India (2006).

[22] Hoa Le-Minh, Zabih Ghassemlooy, Wai Pang Ng. and Razali Ngah, "Terahertz Optical Asymmetric Demultiplexer Switch with a Symmetrical Switching Window" J.Opt.Soc.Am (A) 73(6), 800-808 (1983).

[23] J. Li, L. Li, L. Jin and C. Li, "All-optical switch and limiter based on nonlinear polarization in Mach-Zehnder interferometer coupled with a polarization maintaining fiber-ring resonator," Optics. Communication, 260, 318-323 (2006).

[24] J. N. Roy and S. Mukhopadhyay, "A minimization scheme of optical space variant logic operation in a combinational architecture," Opt.commun. 119, 499-504 (1995).

[25] J. N. Roy, "Mach–Zehnder interferometer-based tree architecture for all-optical logic and arithmetic operations," Optik-International Journal for Light and Electron Optics, 120, 318-324 (2009).

[26] J. P. Sokoloff, P. R. Prucnal, I. Glesk and M. Kane, "A terahertz optical asymmetric demultiplexer (TOAD)," IEEE Photon. Technol. Lett., 5(7), 787-790 (1993).

[27] J. Tanida and Y. Ichioka, "optical logic array processor using shadowgram," J.Opt.Soc.Am (A) 73(6), 800-808 (1983).

[28] J. W. Bruce, M. A. Thornton, L. Shivakumaraiah, P. S. Kokate and X. Li, "Efficient adder circuits based on a conservative reversible logic-gate," IEEE, 83-88, 0-7695-1486-3/02 (2002).

[29] J. Yang, L. Han, H. Zhang and Y. Guo, "Function-lock strategy in OR/NOR optical logic gates based on cross-polarization modulation effect in semiconductor optical amplifier," Chinese Optics Letters, 5 (10), 566-568 (2007).

[30] J. Yang, L. Han, H. Zhang, and Y. Guo, "Function-lock strategy in OR/NOR optical logic gates based on cross-polarization modulation effect in semiconductor optical amplifier," Chin. Opt. Lett. 5, 566-568 (2007).

[31] Jin Yi, He Huacan and Lu Yangtian, "Ternary Optical Computer Architecture," Physica Scripta, T118, 98–101 (2005).

[32] Jitendra Nath Roy, Panchatapa Bhowmik, Tanay Chattopadhyay, "Design of all optical ternary logic based half adder circuit and it's applications" Journal of Optics, Springer India, DOI:10.1007/s12596-015-0279-0 (2015).

[33] K. L. Hall and B. S. Robinson, "Bit error characterization of 100 Gbit/s all-optical demultiplexers," in Proc. Conf. Lasers and Electro-Optics Baltimore, MD, 23–28, 214–215 (1999).

[34] K. R. Chowdhury, S. Mukhopadhyay, "Binary optical arithmetic operation scheme with tree architecture by proper accommodation of optical non-linear materials," Opt. Eng. 43 (1), 132-136 (2004).

[35] K. S. V. Patel and K. S. Gurumurthy, "Arithmetic Operation in Multi valued logic," International Journal of VLSI design & communication system (VLSICS), 1 (1) (2010).

[36] K. Suzuki, K. Iwatsuki, S. Nishi and M. Saruwatari, "Error-free demultiplexing of 160 Gbit/s pulse signal using loop mirror including semiconductor laser amplifier," Electron. Lett., 30 (18), 1501–1503 (1994).

[37] M. A. Karim and A. A. S. Awal, "Optical Computing: an introduction," Wiley, New York (1992).

[38] M. Eiselt, W. Pieper and H. G. Weber, "SLALOM: Semiconductor Laser Amplifier in a Loop mirror," Journal of lightwave Technology, 13(10), 2099-2112 (1995).

[39] M. Haghparast, S. J. Jassbi, K. Navi and O. Hashemipou, "Design of a Novel Reversible Multiplier Circuit Using HNG Gate in Nanotechnology," World Applied Sciences Journal, 3 (6), 974-978 (2008).

[40] M. Kovacevic and A. Acampora, "Benefits of wavelength translation in all-optical clearchannel networks," IEEE J. Select. Areas Commun., 14, 868–88 (1996).

[41] M. T. Hill, et al., "Coupled Mach–Zehnder interferometer memory element," Opt. Lett. 30 (13), 1710–1712 (2005).

[42] P. Ghosh and S. Mukhopadhyay, "Implementation of tristate logic based all optical flip-flop with nonlinear material," Chinese Optics Letters, 3(8), 478-479 (2005).

[43] P. J. Winzer, M. Pfennigbauer, M. M. Strasser and W. R. Leeb, "Optimum filter bandwidth for optically preamplified NRZ receivers," J. Lightwave Technol., 19, 1263–1273 (2001).

[44] Pallavi Singh, Devendra Kr. Tripathi, Shikha Jaiswal and H. K. Dixit, "All-Optical Logic Gates: Designs, Classification, and Comparison" Advances in Optical Technologies, Volume 2014, Article ID 275083, 13 pages, http://dx.doi.org/10.1155/2014/275083 (2014).

[45] R. Schreieck, M. Kwakernaak, H. Jackel, E. Gamper, E. Gini, W. Vogt and H. Melchior, "Ultafast switching dynamics of Mach-Zehnder Interferometer switches," IEEE Photonics Technology Letters, 13(6), 603-605 (2001).

[46] R. Schreieck, M. Kwakernaak, H. Jackel, E. Gamper, E. Gini, W. Vogt and H. Melchior, "Ultafast switching dynamics of Mach-Zehnder Interferometer switches," IEEE Photonics Technology Letters, 13(6), 603-605 (2001).

[47] Rupali Maji and Sourangshu Mukhopadhyay, " An alternative optical method of determining the unknown microwave frequency by the use of electro-optic materials and semiconductor optical amplifier", Optik - International Journal for Light and Electron Optics, Volume 122, Issue 18, Pp. 1622–1624, 2011,

[48] S. Diez, R. Ludwig, and H. G. Weber, "Gain-transparent SOA-switch for high-bitrate OTDM add/drop multiplexing," IEEE Photon. Technol. Lett., 11, 60–62 (1999).

[49] S. H. Kim, J. H. Kim, J. W. Choi, C. W. Son, Y. T. Byun, Y. M. Jhon, S. Lee, D. H. Woo, and S. H. Kim, "All-optical half adder using cross gain modulation in semiconductor optical amplifiers," Optics Express, 14 (22), 10693-10698 (2006).

[50] S. J. Madden et. al., "Four-Channel Polarization-Insensitive Optically Transparent Wavelength Converter," IEEE, 9 (10) (1997).

[51] S. Liu, C. Li, J. Wu and Y. Liu, "Optoelectronic multiple-valued logic implementation," Optics Letters, 14(14), 713-715 (1989).

[52] S. Nakamura, et. al., "Demultiplexing of 168-Gb/s data pulses with a hybrid-integrated symmetric Mach–Zehnder all-optical switch," IEEE Photon. Technol. Lett., 12, 425–427 (2000).

[53] S. Nakamura, Y. Ueno, K. Tajima, J. Sasaki, T. Sugimoto, T. Kato, T. Shimoda, M. Itoh, H. Hatakayama, T. Tamanuki and T. Sasaki, "Demultiplexing of 168-Gb/s data pulses with

a hybrid integrated symmetric Mach– Zehnder all-optical switch," IEEE Photon. 12 (4), 425–427 (2000).

[54] Saibal Mitra, , Sourangshu Mukhopadhyay, "An analytical investigation on the interactions between a squeezed and a coherent optical signal"Optik - International Journal for Light and Electron Optics Volume 124, Issue 20, Pp.4586–4589, 2013.

[55] Somnath Sen and Sourangshu Mukhopadhyay, "A noble technique of using a specially cut LiNbO3 for achieving a greater amount phase difference between the components of light rays", Optik - International Journal for Light and Electron Optics Volume 124, Issue 11, Pp. 1011–1013, 2013.

[56] St. Fischer, M. Dulk, M. Bitter, M. Caraccia, E. Gamper, E. Gini, W. Vogt, H. Melchior, W. Hunziker, A. Buxens, H. N. Paulsenand and A. T. Clausen, "Ultrafast all-optical demultiplexer based on Mach–Zehnder interferometer with integrated semiconductor amplifiers," in: Proceedings of the Fifth Optoelectronic Communication Conference (OECC), Chiba, Japan, 566–567 (2000).

[57] T. Chattopadhyay and J. N. Roy, "All-optical conversion scheme: binary to quaternary and quaternary to binary number," Optics & Laser Technology, doi:10.1016/j.optlastec. 2008.06.003 (2008).

[58] T. Chattopadhyay and J. N. Roy, "Polarization encoded all-optical quaternary multiplexer and demultiplexer -a proposal," Optik, doi:10.1016/j.ijleo.2008.03.030 (2008).

[59] T. Chattopadhyay and J. N. Roy, "Polarization encoded TOAD based all-optical quaternary Literals," Optik (2008).

[60] T. Ivan, "Lima Efficient Computation of Outage Probabilities Due to Polarization Effects in a WDM System Using a Reduced Stokes Model and Importance Sampling IEEE photonics technology letters," 15 (1) (2003).

[61] T. Yatagai, "optical space variant logic gate array based on spatial encoding technique," Opt. Letter, 11, 260-262 (1986).

[62] Tamer A. Moniem and Noha EL Mosilhy, "All Optical OVSF Code Generator Realization using Optical Flip Flop and Optical Hardlimiters" Journal of Engineering Sciences Assiut University Faculty of Engineering, 43 (2), 242 – 252 (2015).

[63] Tanay Chattopadhyay, Cláudia Reis, Paulo André, António Teixeira,"Theoretical analysis of all-optical clocked D flip-flop using a single SOA assisted symmetric MZI" Elsevier, Optics Communications 285, 2266–2275 (2012).

[64] W. K. Choi, Y. T. Moon and Y. W. Choi, "A broadband linearization method using a novel opto-electrical predistorter for radio-over-fiber systems," DOI: 10.1002/mop.25240 (2010).

[65] W. Li, M. Zhang and P.Ye, "Simulation of an all-optical XOR gate with a semiconductor optical amplifier Mach-Zehnder Interferometer sped up by a continuous-wave assistant light," Journal of optical networking, 4(8), 524-530 (2005).

[66] W. Li, M. Zhang and P.Ye, "Simulation of an all-optical XOR gate with a semiconductor optical amplifier Mach-Zehnder Interferometer sped up by a continuous-wave assistant light," Journal of optical networking, 4(8), 524-530 (2005).

[67] Y. D. Wu, M. H. Chen, S. Y. Chen and K. H. Chiang, "A new all-optical switch by using the nonlinear asymmetric Mach-Zehnder waveguide structure," Proc.SPIE, 5646, 325-333 (2005).

[68] Y. J. Jung, S. Lee and N. Park, "All-optical 4-bit gray code to binary coded decimal converter," Proc. of SPIE, 6890, 68900S, doi:10.1117/12.762429 (2008).

[69] Y. K. Huang, I. Glesk, R. Shankar and P. R. Prucnal, "Simultaneous all-optical 3R regeneration scheme with improved scalability using TOAD," Optics Express, 14(22), 10339-10344 (2006).

[70] Yang Ji, Yunchul Chung, D. Sprinzak, M. Heiblum, D. Mahalu, and Hadas Shtrikman, "An Electronic Mach-Zehnder Interferometer" *Nature* 422, 415-418 (2003).

[71] Z. Li, Z. Chen and B. Li, "Optical pulse controlled all-optical logic gates in SiGe/Si multimode interference," Optics Express. 13(3), 1033-1038 (2005).